



P.O. Box 7307, North Brunswick, NJ 08902-7307

Tel: 732-819-0381 Fax: 732-777-5129 E: sanni@globepharma.com
www.globepharma.com, www.maxiblend.net

TABLE-TOP ROTARY TABLET PRESS (MINIPRESS-II)



New MiniPress - II is a Table-top Rotary Tablet Press which can be supplied with 10 station turret suitable for use with B tooling, 8 station turret suitable for use with D tooling or a turret with 5 stations for B tooling and 5 stations for D tooling. All units are imported from India and are completely rebuilt with modifications to meet US standards. Currently, GlobePharma has over 110 units in the North American market.

(continued)

FEATURES:

AC Drive with fixed pulley
Keyed Turret
Variable speed force feeder
Gravity feeder
Two hoppers – one for gravity feeder and another for force feeder
Pre-compression
GMP design
3 ton maximum compression pressure
1 ton pre-compression pressure
One piece upper cam track
Adjustable machine speed
Hard heat treated rollers
Turret fitted with thrust bearing
Safety-interlocked acrylic guards
Hand wheel with clutch and handle outside of the machine
316 Stainless steel turret

Technical Specifications:

	B Tooling	D Tooling
Max. Tablet Diameter:	16mm	25.4mm
Max. Depth of Fill:	17mm	20.5mm
Max. Output:	21,600/hr	17,280 /hr
Maximum Compr. Pressure		3 Tons
Max. Turret Speed:		36 rpm
Min. Turret Speed:		3 rpm
Max. Pre-Compression Pressure		1 Ton
Upper Punch Penetration:		2.5 - 6mm

Electrical Specifications:

D Tooling Machine:

Main Motor: 2HP (1.5kw), 1690 rpm, 220/ 1 Phase or 480V/3 Phase/60 Hz
Force Feeder Motor: 1/8 HP, 110/220V/1 Phase/50/60 Hz.

B Tooling Machine:

Main Motor: 2HP(1.5kw)/1690 rpm/220V/1 Phase (3 wire)/60 Hz
Force Feeder Motor: 1/8 HP, 110/220V/1 Phase/50/60Hz

Machine Dimensions: D460 x W675 x H1060 mm

Crate Dimensions: D600mm x W850mm x H1200mm

Net Weight: 400 Kg

Gross Weight: 575 kg